

DAISY NAL-R



- SVÍTIDLO LED SMD
- těleso svítidla: ocelový plech
- difuzor svítidla: PMMA
- interiérové svítidlo
- připraveno pro smyčkování (mimo 8W, 12W)

220-240V-50/60Hz



IP₂₀



-20+40°C




120°



25 000



NEUTRAL WHITE







DAISY NAL-R 8W NW
GXDS132

DAISY NAL-R 12W NW
GXDS133

DAISY NAL-R 18W NW
GXDS161

DAISY NAL-R 24W NW
GXDS163



- LED 8W ▶ * 50W
- LED 12W ▶ * 70W
- LED 18W ▶ * 110W
- LED 24W ▶ * 140W

						T_c CCT	R_a CRI	$\leftarrow a \rightarrow$ [mm]	$\leftarrow C \rightarrow$ [mm]			DKC
DAISY NAL-R 8W NW	GXDS132	8592660123578	8	600	neutrální bílá	4000K	≥80	255	92	0,45	1/10	218 Kč
DAISY NAL-R 12W NW	GXDS133	8592660123585	12	900	neutrální bílá	4000K	≥80	282	92	0,48	1/10	328 Kč
DAISY NAL-R 18W NW	GXDS161	8592660120133	18	1300	neutrální bílá	4000K	≥80	330	100	0,63	1/10	438 Kč
DAISY NAL-R 24W NW	GXDS163	8592660120157	24	1800	neutrální bílá	4000K	≥80	375	106	0,85	1/5	504 Kč