



Product Service

Attestation of Conformity

No. N8A 089086 0109 Rev. 02

Holder of Certificate: **BOKE Drivers Co., Ltd.**
2nd and 3rd Floor, No.51, Xihuan 5th Road
South District
528455 Zhongshan City, Guangdong
PEOPLE'S REPUBLIC OF CHINA

Product: **Power supplies**
(Dimmable Constant Current LED Driver)

This Attestation of Conformity is issued on a voluntary basis according to the Low Voltage Directive 2014/35/EU relating to electrical equipment designed for use within certain voltage limits. It confirms that the listed equipment complies with the principal protection requirements of the directive and is based on the technical specifications applicable at the time of issuance. It refers only to the particular sample submitted for testing and certification. For details see: www.tuvsud.com/ps-cert

Test report no.: 651402102403

Date, 2022-06-09

(Taylor Yao)

Page 1 of 5

After preparation of the necessary technical documentation as well as the EU declaration of conformity the required CE marking can be affixed on the product. The declaration of conformity is issued under the sole responsibility of the manufacturer. Other relevant EU-directives have to be observed.



Product Service

Attestation of Conformity

No. N8A 089086 0109 Rev. 02

Model(s): BK-DEL030-0800Ad; BK-DEL042-1100Ad;
BK-DEL042-0800Bd; BK-DEL060-2000Ad;
BK-DEL030-B0800Ad; BK-DEL042-B1100Ad;
BK-DEL060-B2000Ad; BK-DEL010-0350Ad;
BK-DEL022-0600Ad; BK-DEL028-0750Ad

Brand: BOKE



Parameters:

Rated Input Voltage: 200-240V AC/DC
Rated Frequency: 0/50/60Hz
Rated Input Current: See below table for details
Rated Output: See below table for details
Protection against Electric Shock: Class II; SELV
Degree of Protection: IP20
Method of Installation: Independent
Type of Output: Constant current type
ta: See below table for details
tc: 90°C

Tested according to: EN 61347-1:2015/A1:2021
EN 61347-2-13:2014/A1:2017
EN 62493:2015

Page 2 of 5

After preparation of the necessary technical documentation as well as the EU declaration of conformity the required CE marking can be affixed on the product. The declaration of conformity is issued under the sole responsibility of the manufacturer. Other relevant EU-directives have to be observed.



Attestation of Conformity

No. N8A 089086 0109 Rev. 02

| Model | Rated Input Current (A) Max. | Output Voltage (VDC) | I _{rated} (mA) | P _{rated} (W) | U _{out} (VDC) | ta (°C) |
|------------------|------------------------------|----------------------|-------------------------|------------------------|------------------------|---------|
| BK-DEL030-0800Ad | 0.18 | 6-42 | 250 | 10.5 | 50 | 45 |
| | | 6-42 | 275 | 11.55 | | |
| | | 6-42 | 300 | 12.6 | | |
| | | 6-42 | 325 | 13.65 | | |
| | | 6-42 | 350 | 14.7 | | |
| | | 6-42 | 375 | 15.75 | | |
| | | 6-42 | 400 | 16.8 | | |
| | | 6-42 | 425 | 17.85 | | |
| | | 6-42 | 450 | 18.9 | | |
| | | 6-42 | 500 | 21 | | |
| | | 6-42 | 550 | 23.1 | | |
| | | 6-42 | 600 | 25.2 | | |
| | | 6-42 | 650 | 27.3 | | |
| | | 6-42 | 700 | 29.4 | | |
| | | 6-40 | 750 | 30 | | |
| 6-38 | 800 | 30.4 | | | | |
| BK-DEL042-1100Ad | 0.25 | 6-42 | 450 | 18.9 | 50 | 45 |
| | | 6-42 | 475 | 19.95 | | |
| | | 6-42 | 500 | 21 | | |
| | | 6-42 | 525 | 22.05 | | |
| | | 6-42 | 550 | 23.1 | | |
| | | 6-42 | 600 | 25.2 | | |
| | | 6-42 | 650 | 27.3 | | |
| | | 6-42 | 700 | 29.4 | | |
| | | 6-42 | 750 | 31.5 | | |
| | | 6-42 | 800 | 33.6 | | |
| | | 6-42 | 850 | 35.7 | | |
| | | 6-42 | 900 | 37.8 | | |
| | | 6-42 | 950 | 39.9 | | |
| | | 6-42 | 1000 | 42 | | |
| | | 6-40 | 1050 | 42 | | |
| 6-38 | 1100 | 41.8 | | | | |
| BK-DEL042-0800Bd | 0.25 | 6-84 | 250 | 21 | 100 | 45 |
| | | 6-84 | 275 | 23.1 | | |
| | | 6-84 | 300 | 25.2 | | |
| | | 6-84 | 325 | 27.3 | | |
| | | 6-84 | 350 | 29.4 | | |
| | | 6-84 | 375 | 31.5 | | |
| | | 6-84 | 400 | 33.6 | | |
| | | 6-84 | 425 | 35.7 | | |
| | | 6-84 | 450 | 37.8 | | |
| | | 6-84 | 500 | 42 | | |
| | | 6-76 | 550 | 41.8 | | |
| | | 6-70 | 600 | 42 | | |
| | | 6-64 | 650 | 41.6 | | |
| | | 6-60 | 700 | 42 | | |
| | | 6-54 | 750 | 42 | | |



Attestation of Conformity

No. N8A 089086 0109 Rev. 02

| | | | | | | |
|-------------------|------|------|------|-------|----|----|
| BK-DEL060-2000Ad | 0.36 | 6-52 | 800 | 41.6 | 50 | 45 |
| | | 6-42 | 800 | 33.6 | | |
| | | 6-42 | 900 | 37.8 | | |
| | | 6-42 | 1000 | 42 | | |
| | | 6-42 | 1050 | 44.1 | | |
| | | 6-42 | 1100 | 46.2 | | |
| | | 6-42 | 1150 | 48.3 | | |
| | | 6-42 | 1200 | 50.4 | | |
| | | 6-42 | 1250 | 52.5 | | |
| | | 6-42 | 1300 | 54.6 | | |
| | | 6-42 | 1400 | 58.8 | | |
| | | 6-40 | 1500 | 60 | | |
| | | 6-38 | 1600 | 60.8 | | |
| | | 6-36 | 1700 | 61.2 | | |
| | | 6-34 | 1800 | 61.2 | | |
| | | 6-32 | 1900 | 60.8 | | |
| 6-30 | 2000 | 60 | | | | |
| BK-DEL030-B0800Ad | 0.18 | 6-42 | 250 | 10.5 | 50 | 45 |
| | | 6-42 | 275 | 11.55 | | |
| | | 6-42 | 300 | 12.6 | | |
| | | 6-42 | 325 | 13.65 | | |
| | | 6-42 | 350 | 14.7 | | |
| | | 6-42 | 375 | 15.75 | | |
| | | 6-42 | 400 | 16.8 | | |
| | | 6-42 | 425 | 17.85 | | |
| | | 6-42 | 450 | 18.9 | | |
| | | 6-42 | 500 | 21 | | |
| | | 6-42 | 550 | 23.1 | | |
| | | 6-42 | 600 | 25.2 | | |
| | | 6-42 | 650 | 27.3 | | |
| | | 6-42 | 700 | 29.4 | | |
| | | 6-40 | 750 | 30 | | |
| | | 6-38 | 800 | 30.4 | | |
| BK-DEL042-B1100Ad | 0.25 | 6-42 | 450 | 18.9 | 50 | 45 |
| | | 6-42 | 475 | 19.95 | | |
| | | 6-42 | 500 | 21 | | |
| | | 6-42 | 525 | 22.05 | | |
| | | 6-42 | 550 | 23.1 | | |
| | | 6-42 | 600 | 25.2 | | |
| | | 6-42 | 650 | 27.3 | | |
| | | 6-42 | 700 | 29.4 | | |
| | | 6-42 | 750 | 31.5 | | |
| | | 6-42 | 800 | 33.6 | | |
| | | 6-42 | 850 | 35.7 | | |
| | | 6-42 | 900 | 37.8 | | |
| | | 6-42 | 950 | 39.9 | | |
| | | 6-42 | 1000 | 42 | | |
| | | 6-40 | 1050 | 42 | | |
| | | 6-38 | 1100 | 41.8 | | |



Attestation of Conformity

No. N8A 089086 0109 Rev. 02

| | | | | | | |
|-------------------|------|------|------|-------|----|----|
| BK-DEL060-B2000Ad | 0.36 | 6-42 | 800 | 33.6 | 50 | 45 |
| | | 6-42 | 900 | 37.8 | | |
| | | 6-42 | 1000 | 42 | | |
| | | 6-42 | 1050 | 44.1 | | |
| | | 6-42 | 1100 | 46.2 | | |
| | | 6-42 | 1150 | 48.3 | | |
| | | 6-42 | 1200 | 50.4 | | |
| | | 6-42 | 1250 | 52.5 | | |
| | | 6-42 | 1300 | 54.6 | | |
| | | 6-42 | 1400 | 58.8 | | |
| | | 6-40 | 1500 | 60 | | |
| | | 6-38 | 1600 | 60.8 | | |
| | | 6-36 | 1700 | 61.2 | | |
| | | 6-34 | 1800 | 61.2 | | |
| | | 6-32 | 1900 | 60.8 | | |
| 6-30 | 2000 | 60 | | | | |
| BK-DEL010-0350Ad | 0.07 | 6-42 | 100 | 4.2 | 50 | 60 |
| | | 6-42 | 125 | 5.25 | | |
| | | 6-42 | 150 | 6.3 | | |
| | | 6-42 | 175 | 7.35 | | |
| | | 6-42 | 200 | 8.4 | | |
| | | 6-42 | 225 | 9.45 | | |
| | | 6-42 | 250 | 10.5 | | |
| | | 6-40 | 275 | 11.0 | | |
| | | 6-36 | 300 | 10.8 | | |
| | | 6-30 | 350 | 10.5 | | |
| BK-DEL022-0600Ad | 0.14 | 6-42 | 225 | 9.45 | 50 | 50 |
| | | 6-42 | 250 | 10.5 | | |
| | | 6-42 | 275 | 11.55 | | |
| | | 6-42 | 300 | 12.6 | | |
| | | 6-42 | 350 | 14.7 | | |
| | | 6-42 | 400 | 16.8 | | |
| | | 6-42 | 450 | 18.9 | | |
| | | 6-42 | 500 | 21.0 | | |
| | | 6-42 | 550 | 23.1 | | |
| | | 6-38 | 600 | 22.8 | | |
| BK-DEL028-0750Ad | 0.18 | 6-42 | 300 | 12.6 | 50 | 45 |
| | | 6-42 | 350 | 14.7 | | |
| | | 6-42 | 400 | 16.8 | | |
| | | 6-42 | 450 | 18.9 | | |
| | | 6-42 | 500 | 21.0 | | |
| | | 6-42 | 550 | 23.1 | | |
| | | 6-42 | 600 | 25.2 | | |
| | | 6-42 | 650 | 27.3 | | |
| | | 6-40 | 700 | 28.0 | | |
| 6-38 | 750 | 28.5 | | | | |



Product Service

Attestation of Conformity

No. E8A 089086 0208 Rev. 00

Holder of Certificate: **BOKE Drivers Co., Ltd.**
2nd and 3rd Floor, No.51, Xihuan 5th Road
South District
528455 Zhongshan City, Guangdong
PEOPLE'S REPUBLIC OF CHINA

Name of Object: **Power supplies**
(Dimmable Constant Current LED Driver)

This Attestation of Conformity is issued on a voluntary basis according to the Directive 2014/30/EU relating to electromagnetic compatibility. It confirms that the listed apparatus complies with all essential requirements of the directive and is based on the technical specifications applicable at the time of issuance. It refers only to the particular sample submitted for testing and certification. For details see: www.tuvsud.com/ps-cert

Test report no.: 657402201401

Date, 2022-06-14

(Laurent Yuan)

Page 1 of 4

After preparation of the necessary technical documentation as well as the EU Declaration of conformity the required CE marking can be affixed on the product. That Declaration of conformity is issued under the sole responsibility of the manufacturer. Other relevant EU-directives have to be observed.



Product Service

Attestation of Conformity

No. E8A 089086 0208 Rev. 00

Model(s): BK-DEL030-B0800Ad; BK-DEL042-B1100Ad;
BK-DEL060-B2000Ad

Description of

Object:

Rated Input Voltage: 200-240V AC/DC

Rated Frequency: 0/50/60Hz

Rated Input Current: See below table for details

Rated Output: See below table for details

Protection Class: II

**Tested
according to:**

EN IEC 55015:2019/A11:2020

EN IEC 61000-3-2:2019/A1:2021

EN 61000-3-3:2013/A2:2021

EN 61547:2009

Page 2 of 4

After preparation of the necessary technical documentation as well as the EU Declaration of conformity the required CE marking can be affixed on the product. That Declaration of conformity is issued under the sole responsibility of the manufacturer. Other relevant EU-directives have to be observed.



Attestation of Conformity

No. E8A 089086 0208 Rev. 00

| Model | Rated Input Current (A) Max. | Output Voltage (VDC) | I _{rated} (mA) | P _{rated} (W) | U _{out} (VDC) |
|-------------------|------------------------------|----------------------|-------------------------|------------------------|------------------------|
| BK-DEL030-B0800Ad | 0.18 | 6-42 | 250 | 10.5 | 50 |
| | | 6-42 | 275 | 11.55 | |
| | | 6-42 | 300 | 12.6 | |
| | | 6-42 | 325 | 13.65 | |
| | | 6-42 | 350 | 14.7 | |
| | | 6-42 | 375 | 15.75 | |
| | | 6-42 | 400 | 16.8 | |
| | | 6-42 | 425 | 17.85 | |
| | | 6-42 | 450 | 18.9 | |
| | | 6-42 | 500 | 21 | |
| | | 6-42 | 550 | 23.1 | |
| | | 6-42 | 600 | 25.2 | |
| | | 6-42 | 650 | 27.3 | |
| | | 6-42 | 700 | 29.4 | |
| | | 6-40 | 750 | 30 | |
| 6-38 | 800 | 30.4 | | | |
| BK-DEL042-B1100Ad | 0.25 | 6-42 | 450 | 18.9 | 50 |
| | | 6-42 | 475 | 19.95 | |
| | | 6-42 | 500 | 21 | |
| | | 6-42 | 525 | 22.05 | |
| | | 6-42 | 550 | 23.1 | |
| | | 6-42 | 600 | 25.2 | |
| | | 6-42 | 650 | 27.3 | |
| | | 6-42 | 700 | 29.4 | |
| | | 6-42 | 750 | 31.5 | |
| | | 6-42 | 800 | 33.6 | |
| | | 6-42 | 850 | 35.7 | |
| | | 6-42 | 900 | 37.8 | |
| | | 6-42 | 950 | 39.9 | |
| | | 6-42 | 1000 | 42 | |
| | | 6-40 | 1050 | 42 | |
| 6-38 | 1100 | 41.8 | | | |

After preparation of the necessary technical documentation as well as the EU Declaration of conformity the required CE marking can be affixed on the product. That Declaration of conformity is issued under the sole responsibility of the manufacturer. Other relevant EU-directives have to be observed.



Product Service

Attestation of Conformity

No. E8A 089086 0208 Rev. 00

| | | | | | |
|-------------------|------|------|------|------|----|
| BK-DEL060-B2000Ad | 0.36 | 6-42 | 800 | 33.6 | 50 |
| | | 6-42 | 900 | 37.8 | |
| | | 6-42 | 1000 | 42 | |
| | | 6-42 | 1050 | 44.1 | |
| | | 6-42 | 1100 | 46.2 | |
| | | 6-42 | 1150 | 48.3 | |
| | | 6-42 | 1200 | 50.4 | |
| | | 6-42 | 1250 | 52.5 | |
| | | 6-42 | 1300 | 54.6 | |
| | | 6-42 | 1400 | 58.8 | |
| | | 6-40 | 1500 | 60 | |
| | | 6-38 | 1600 | 60.8 | |
| | | 6-36 | 1700 | 61.2 | |
| | | 6-34 | 1800 | 61.2 | |
| | | 6-32 | 1900 | 60.8 | |
| | | 6-30 | 2000 | 60 | |

Page 4 of 4

After preparation of the necessary technical documentation as well as the EU Declaration of conformity the required CE marking can be affixed on the product. That Declaration of conformity is issued under the sole responsibility of the manufacturer. Other relevant EU-directives have to be observed.

CERTIFICATE

No. U6 089086 0111 Rev. 02

Holder of Certificate: **BOKE Drivers Co., Ltd.**
2nd and 3rd Floor, No.51, Xihuan 5th Road
South District
528455 Zhongshan City, Guangdong
PEOPLE'S REPUBLIC OF CHINA

Certification Mark:




Product: **Power supplies**
(Dimmable Constant Current LED Driver)

The product was voluntarily tested according to the listed standards. The product can be marked with the certification mark shown above. It is not permitted to alter the certification mark in any way. In addition, the certificate holder must not transfer the certificate to third parties. All applicable requirements of the testing and certification regulations of TÜV SÜD Group have to be complied. For details see: www.tuvsud.com/ps-cert

Test report no.: 64142215000903

Date, 2022-06-15



(Taylor Yao)

CERTIFICATE

No. U6 089086 0111 Rev. 02

Model(s): BK-DEL030-0800Ad; BK-DEL042-1100Ad;
BK-DEL042-0800Bd; BK-DEL060-2000Ad;
BK-DEL030-B0800Ad; BK-DEL042-B1100Ad;
BK-DEL060-B2000Ad; BK-DEL010-0350Ad;
BK-DEL022-0600Ad; BK-DEL028-0750Ad

Brand Name: BOKE



Parameters:

Rated Input Voltage: 200-240V AC/DC
Rated Frequency: 0/50/60Hz
Rated Input Current: See below table for details
Rated Output: See below table for details
Protection against Electric Shock: Class II; SELV
Degree of Protection: IP20
Method of Installation: Independent
Type of Output: Constant current type
ta: See below table for details
tc: 90°C

Tested according to: EN 61347-1:2015/A1:2021
EN 61347-2-13:2014/A1:2017
EN IEC 62384:2020

Production Facility(ies): 089086

CERTIFICATE

No. U6 089086 0111 Rev. 02

| Model | Rated Input Current (A) Max. | Output Voltage (VDC) | I _{rated} (mA) | P _{rated} (W) | U _{out} (VDC) | ta (°C) |
|------------------|------------------------------|----------------------|-------------------------|------------------------|------------------------|---------|
| BK-DEL030-0800Ad | 0.18 | 6-42 | 250 | 10.5 | 50 | 45 |
| | | 6-42 | 275 | 11.55 | | |
| | | 6-42 | 300 | 12.6 | | |
| | | 6-42 | 325 | 13.65 | | |
| | | 6-42 | 350 | 14.7 | | |
| | | 6-42 | 375 | 15.75 | | |
| | | 6-42 | 400 | 16.8 | | |
| | | 6-42 | 425 | 17.85 | | |
| | | 6-42 | 450 | 18.9 | | |
| | | 6-42 | 500 | 21 | | |
| | | 6-42 | 550 | 23.1 | | |
| | | 6-42 | 600 | 25.2 | | |
| | | 6-42 | 650 | 27.3 | | |
| | | 6-42 | 700 | 29.4 | | |
| BK-DEL042-1100Ad | 0.25 | 6-40 | 750 | 30 | 50 | 45 |
| | | 6-38 | 800 | 30.4 | | |
| | | 6-42 | 450 | 18.9 | | |
| | | 6-42 | 475 | 19.95 | | |
| | | 6-42 | 500 | 21 | | |
| | | 6-42 | 525 | 22.05 | | |
| | | 6-42 | 550 | 23.1 | | |
| | | 6-42 | 600 | 25.2 | | |
| | | 6-42 | 650 | 27.3 | | |
| | | 6-42 | 700 | 29.4 | | |
| | | 6-42 | 750 | 31.5 | | |
| | | 6-42 | 800 | 33.6 | | |
| | | 6-42 | 850 | 35.7 | | |
| | | 6-42 | 900 | 37.8 | | |
| 6-42 | 950 | 39.9 | | | | |
| BK-DEL042-0800Bd | 0.25 | 6-42 | 1000 | 42 | 100 | 45 |
| | | 6-40 | 1050 | 42 | | |
| | | 6-38 | 1100 | 41.8 | | |
| | | 6-84 | 250 | 21 | | |
| | | 6-84 | 275 | 23.1 | | |
| | | 6-84 | 300 | 25.2 | | |
| | | 6-84 | 325 | 27.3 | | |
| | | 6-84 | 350 | 29.4 | | |
| | | 6-84 | 375 | 31.5 | | |
| | | 6-84 | 400 | 33.6 | | |
| | | 6-84 | 425 | 35.7 | | |
| | | 6-84 | 450 | 37.8 | | |
| | | 6-84 | 500 | 42 | | |
| | | 6-76 | 550 | 41.8 | | |
| | | 6-70 | 600 | 42 | | |
| | | 6-64 | 650 | 41.6 | | |
| 6-60 | 700 | 42 | | | | |
| 6-54 | 750 | 42 | | | | |
| 6-52 | 800 | 41.6 | | | | |

CERTIFICATE

No. U6 089086 0111 Rev. 02

ZERTIFIKAT ◆ CERTIFICATE ◆ 認證證書 ◆ СЕРТИФИКАТ ◆ CERTIFICADO ◆ CERTIFICAT

| | | | | | | |
|-------------------|------|------|------|-------|----|----|
| BK-DEL060-2000Ad | 0.36 | 6-42 | 800 | 33.6 | 50 | 45 |
| | | 6-42 | 900 | 37.8 | | |
| | | 6-42 | 1000 | 42 | | |
| | | 6-42 | 1050 | 44.1 | | |
| | | 6-42 | 1100 | 46.2 | | |
| | | 6-42 | 1150 | 48.3 | | |
| | | 6-42 | 1200 | 50.4 | | |
| | | 6-42 | 1250 | 52.5 | | |
| | | 6-42 | 1300 | 54.6 | | |
| | | 6-42 | 1400 | 58.8 | | |
| | | 6-40 | 1500 | 60 | | |
| | | 6-38 | 1600 | 60.8 | | |
| | | 6-36 | 1700 | 61.2 | | |
| | | 6-34 | 1800 | 61.2 | | |
| | | 6-32 | 1900 | 60.8 | | |
| 6-30 | 2000 | 60 | | | | |
| BK-DEL030-B0800Ad | 0.18 | 6-42 | 250 | 10.5 | 50 | 45 |
| | | 6-42 | 275 | 11.55 | | |
| | | 6-42 | 300 | 12.6 | | |
| | | 6-42 | 325 | 13.65 | | |
| | | 6-42 | 350 | 14.7 | | |
| | | 6-42 | 375 | 15.75 | | |
| | | 6-42 | 400 | 16.8 | | |
| | | 6-42 | 425 | 17.85 | | |
| | | 6-42 | 450 | 18.9 | | |
| | | 6-42 | 500 | 21 | | |
| | | 6-42 | 550 | 23.1 | | |
| | | 6-42 | 600 | 25.2 | | |
| | | 6-42 | 650 | 27.3 | | |
| | | 6-42 | 700 | 29.4 | | |
| | | 6-40 | 750 | 30 | | |
| 6-38 | 800 | 30.4 | | | | |
| BK-DEL042-B1100Ad | 0.25 | 6-42 | 450 | 18.9 | 50 | 45 |
| | | 6-42 | 475 | 19.95 | | |
| | | 6-42 | 500 | 21 | | |
| | | 6-42 | 525 | 22.05 | | |
| | | 6-42 | 550 | 23.1 | | |
| | | 6-42 | 600 | 25.2 | | |
| | | 6-42 | 650 | 27.3 | | |
| | | 6-42 | 700 | 29.4 | | |
| | | 6-42 | 750 | 31.5 | | |
| | | 6-42 | 800 | 33.6 | | |
| | | 6-42 | 850 | 35.7 | | |
| | | 6-42 | 900 | 37.8 | | |
| | | 6-42 | 950 | 39.9 | | |
| | | 6-42 | 1000 | 42 | | |
| | | 6-40 | 1050 | 42 | | |
| 6-38 | 1100 | 41.8 | | | | |

CERTIFICATE

No. U6 089086 0111 Rev. 02

ZERTIFIKAT ◆ CERTIFICATE ◆ 認 證 證 書 ◆ CERTIFICADO ◆ СЕРТИФИКАТ ◆ CERTIFICAT

| | | | | | | |
|-------------------|------|------|------|-------|----|----|
| BK-DEL060-B2000Ad | 0.36 | 6-42 | 800 | 33.6 | 50 | 45 |
| | | 6-42 | 900 | 37.8 | | |
| | | 6-42 | 1000 | 42 | | |
| | | 6-42 | 1050 | 44.1 | | |
| | | 6-42 | 1100 | 46.2 | | |
| | | 6-42 | 1150 | 48.3 | | |
| | | 6-42 | 1200 | 50.4 | | |
| | | 6-42 | 1250 | 52.5 | | |
| | | 6-42 | 1300 | 54.6 | | |
| | | 6-42 | 1400 | 58.8 | | |
| | | 6-40 | 1500 | 60 | | |
| | | 6-38 | 1600 | 60.8 | | |
| | | 6-36 | 1700 | 61.2 | | |
| | | 6-34 | 1800 | 61.2 | | |
| | | 6-32 | 1900 | 60.8 | | |
| 6-30 | 2000 | 60 | | | | |
| BK-DEL010-0350Ad | 0.07 | 6-42 | 100 | 4.2 | 50 | 60 |
| | | 6-42 | 125 | 5.25 | | |
| | | 6-42 | 150 | 6.3 | | |
| | | 6-42 | 175 | 7.35 | | |
| | | 6-42 | 200 | 8.4 | | |
| | | 6-42 | 225 | 9.45 | | |
| | | 6-42 | 250 | 10.5 | | |
| | | 6-40 | 275 | 11.0 | | |
| | | 6-36 | 300 | 10.8 | | |
| | | 6-30 | 350 | 10.5 | | |
| BK-DEL022-0600Ad | 0.14 | 6-42 | 225 | 9.45 | 50 | 50 |
| | | 6-42 | 250 | 10.5 | | |
| | | 6-42 | 275 | 11.55 | | |
| | | 6-42 | 300 | 12.6 | | |
| | | 6-42 | 350 | 14.7 | | |
| | | 6-42 | 400 | 16.8 | | |
| | | 6-42 | 450 | 18.9 | | |
| | | 6-42 | 500 | 21.0 | | |
| | | 6-42 | 550 | 23.1 | | |
| 6-38 | 600 | 22.8 | | | | |



CERTIFICATE

No. U6 089086 0111 Rev. 02

| | | | | | | |
|------------------|------|------|-----|------|----|----|
| BK-DEL028-0750Ad | 0.18 | 6-42 | 300 | 12.6 | 50 | 45 |
| | | 6-42 | 350 | 14.7 | | |
| | | 6-42 | 400 | 16.8 | | |
| | | 6-42 | 450 | 18.9 | | |
| | | 6-42 | 500 | 21.0 | | |
| | | 6-42 | 550 | 23.1 | | |
| | | 6-42 | 600 | 25.2 | | |
| | | 6-42 | 650 | 27.3 | | |
| | | 6-40 | 700 | 28.0 | | |
| | | 6-38 | 750 | 28.5 | | |