

Greenlux lights	I rated (CC) & Voltage DC	Pcs	I-sel Resistor	switchDIM driver GXOS215 Tridonic LCA 45W driver 500-1400mA; 25-50V
		1	x	☒
LED60 VEGA 12W	300mA; 24-42V	2<	8,33kΩ (600mA)	☑
		1	8,33kΩ	☑
LED90 VEGA 18W	600mA; 20-30V	2<	4,17kΩ (1200mA)	☑
		1	8,33kΩ	☑
LED120 VEGA 24W	600mA; 30-45V	2	x	☒
LINX PROFI 20W	500mA; 25-40V	1	open	☑
LINX PROFI 30W	750mA; 33-40V	1	6,67kΩ	☑
LINX PROFI 40W	1000mA; 33-40V	1	5,00kΩ	☑
VIRGO PROFI 36W N2B	900mA; 30-42V	1	5,56kΩ	☑
VIRGO PROFI 36W N4B	900mA; 30-42V	1	5,56kΩ	☑
VIRGO PROFI 45W N4B	1050mA; 32-42V	1	4,76kΩ	☑
VIRGO PROFI MINI 36W N2B	900mA; 30-42V	1	5,56kΩ	☑
LED VIRGO-5 840 40W	960mA; 36-42V	1	5,26kΩ	☑
DAISY VIRGO 40W/WF	1000mA; 36-42V	1	5,00kΩ	☑
DAISY LED VIRGO 840-45W/WF	1100mA; 36-42V	1	4,55kΩ	☑
LED VIRGO II-840 40W	960mA; 36-42V	1	5,26kΩ	☑
DAISY VIRGO II 840-40W/WF	1000mA; 36-42V	1	5,00kΩ	☑
DAISY LIBRA 36W NW	900mA; 27-42V	1	5,56kΩ	☑

